

Horizontal Sidewall Fire Sprinkler Standard Response K5.6 1/2"

UL Listed Horizontal Sidewall Fire Sprinklers, Standard Response, 5mm Glass Bulb, K5.6, 1/2" Connecting Thread.
Model: KS805

Standard Coverage, Standard Response, 5mm Glass Bulb, K5.6, 1/2" Connecting Thread.

UL Listed KSFCO Standard Coverage Horizontal Sidewall Sprinklers are glass-bulb types designed for use in various commercial applications. The temperature range of 5mm and 3mm glass bulb is from: 135°F/57°C, 155°F /68°C, 175°F/79°C, 200°F/93°C up to 286°F/141°C.

Bulb Nominal Dia.& Response	Ø5mm Standard Response
Thread Size	NPT1/2" or BSPT1/2"
Nominal Orifice Size	1/2 Inch
Nominal K-Factor	5.6 (U.S.)/80 (metric)
Max. Working Pressure	175psig/1.2MPa (12bar)
Sprinkler Finish	Natural Brass, Chrome Finished or White Painting (RAL9010)
Nominal Temp. Rating °F (°C)	135°F/(57°C) 155°F/(68°C) 175°F/(79°C) 200°F/(93°C) 286°F/(141°C)
Listing and Approvals	UL Listed

Horizontal Sidewall Fire Sprinkler Quick Response K5.6 1/2"

UL Listed Horizontal Sidewall Fire Sprinklers Standard Coverage, Quick Response, 3mm Glass Bulb, K5.6, 1/2" Connecting Thread.
Model: KS806

Standard Coverage, Quick Response, 3mm Glass Bulb, K5.6, 1/2" Connecting Thread.

UL Listed KSFCO Standard Coverage Horizontal Sidewall Sprinklers are glass-bulb types designed for use in various commercial applications.

KSFCO Horizontal Sidewall Sprinklers launched in year 2020 with standard response and quick response.

The temperature range of 5mm and 3mm glass ball is from :

135°F/57°C, 155°F /68°C, 175°F/79°C, 200°F/93°C up to 286°F/141°C.

Bulb Nominal Dia.& Response	Ø3mm Quick Response
Thread Size	NPT1/2" or BSPT1/2"
Nominal Orifice Size	1/2 Inch
Nominal K-Factor	5.6 (U.S.)/80 (metric)
Max. Working Pressure	175psi/1.2MPa (12bar)
Sprinkler Finish	Natural Brass, Chrome Finished or White Painting (RAL9010)
Nominal Temp. Rating °F (°C)	135°F/(57°C) 155°F/(68°C) 175°F/(79°C) 200°F/(93°C) 286°F/(141°C)
Listing and Approvals	UL Listed



**SIDEWALL
STANDARD
SPRINKLERS**



**SIDEWALL
QUICK RESPONSE
SPRINKLERS**



www.shieldfirefighting.com



Location : North Al Batinah governorate, Sohar FZ ,Oman

Contact US: 0096871714938